

ALUMINUM ELECTROLYTIC CAPACITORS


nichicon

UUD

Chip Type, Low Impedance



- Chip type, low impedance temperature range up to +105°C.
- Designed for surface mounting on high density PC board.
- Applicable to automatic mounting machine fed with carrier tape.
- Compliant to the RoHS directive (2011/65/EU,(EU)2015/863).
- AEC-Q200 compliant. Please contact us for details.




■ Specifications


Item	Performance Characteristics																										
Category Temperature Range	−55 to +105°C																										
Rated Voltage Range	6.3 to 50V																										
Rated Capacitance Range	1 to 1500μF																										
Capacitance Tolerance	±20% at 120Hz, 20°C																										
Leakage Current	After 2 minutes' application of rated voltage at 20°C, leakage current is not more than 0.01 CV or 3 (μA), whichever is greater.																										
Tangent of loss angle (tan δ)	Measurement frequency : 120Hz at 20°C <table border="1"> <tr> <th>Rated voltage (V)</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> </tr> <tr> <td>tan δ (MAX.)</td> <td>0.26 (0.28)</td> <td>0.20 (0.24)</td> <td>0.16 (0.20)</td> <td>0.14 (0.16)</td> <td>0.12 (0.14)</td> <td>0.12 (0.14)</td> </tr> </table> () is φ8 over						Rated voltage (V)	6.3	10	16	25	35	50	tan δ (MAX.)	0.26 (0.28)	0.20 (0.24)	0.16 (0.20)	0.14 (0.16)	0.12 (0.14)	0.12 (0.14)							
Rated voltage (V)	6.3	10	16	25	35	50																					
tan δ (MAX.)	0.26 (0.28)	0.20 (0.24)	0.16 (0.20)	0.14 (0.16)	0.12 (0.14)	0.12 (0.14)																					
Stability at Low Temperature	Measurement frequency : 120Hz <table border="1"> <tr> <th>Rated voltage (V)</th> <th>6.3</th> <th>10</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> </tr> <tr> <td>Impedance ratio Z-25°C / Z+20°C</td> <td>3</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> <td>2</td> </tr> <tr> <td>ZT / Z20 (MAX.)</td> <td>5</td> <td>4</td> <td>4</td> <td>3</td> <td>3</td> <td>3</td> </tr> </table>						Rated voltage (V)	6.3	10	16	25	35	50	Impedance ratio Z-25°C / Z+20°C	3	2	2	2	2	2	ZT / Z20 (MAX.)	5	4	4	3	3	3
Rated voltage (V)	6.3	10	16	25	35	50																					
Impedance ratio Z-25°C / Z+20°C	3	2	2	2	2	2																					
ZT / Z20 (MAX.)	5	4	4	3	3	3																					
Endurance	The specifications listed at right shall be met when the capacitors are restored to 20°C after the rated voltage is applied for 5000 hours (2000 hours for φD = 4, 5 and 6.3) at 105°C.			Capacitance change	Within ±30% of the initial capacitance value																						
				tan δ	200% or less than the initial specified value																						
				Leakage current	Less than or equal to the initial specified value																						
Shelf Life	After storing the capacitors under no load at 105°C for 1000 hours and then performing voltage treatment based on JIS C 5101-4 clause 4.1 at 20°C, they shall meet the specified values for the endurance characteristics listed above.																										
Resistance to soldering heat	The capacitors are kept on a hot plate for 30 seconds, which is maintained at 250°C. The capacitors shall meet the characteristic requirements listed at right when they are removed from the plate and restored to 20°C.			Capacitance change	Within ±10% of the initial capacitance value																						
				tan δ	Less than or equal to the initial specified value																						
Marking	Black print on the case top.																										

■ Chip Type

(φ4 to φ6.3)




(φ8,φ10)



Voltage

V	6.3	10	16	25	35	50
Code	j	A	C	E	V	H

Type numbering system (Example : 16V 22μF)



φ D × L	4 × 5.8	5 × 5.8	6.3 × 5.8	6.3 × 7.7	8 × 10	10 × 10
A	1.8	2.1	2.4	2.4	2.9	3.2
B	4.3	5.3	6.6	6.6	8.3	10.3
C	4.3	5.3	6.6	6.6	8.3	10.3
E	1.0	1.3	2.2	2.2	3.1	4.5
L	5.8	5.8	5.8	7.7	10	10
H	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.5 to 0.8	0.8 to 1.1	0.8 to 1.1

● Frequency coefficient of rated ripple current

Frequency	50 Hz	120 Hz	300 Hz	1 kHz	10 kHz or more
Coefficient	0.35	0.50	0.64	0.83	1.00

● Dimension table in next page.

CAT.8100J

UUD

■ Dimensions

Rated Voltage (V) (code)	Rated Capacitance (μ F)	Case Size ϕ D×L(mm)	$\tan \delta$	Leakage Current (μ A) (at 20°C after 2 minutes)	Impedance (Ω) MAX. (20°C/100kHz)	Rated Ripple (mArms) (105°C/100kHz)	Part Number
6.3 (0J)	27	4×5.8	0.26	3	1.80	80	UUU0J270MCL1GS
	33	5×5.8	0.26	3	0.76	150	UUU0J330MCL1GS
	47	5×5.8	0.26	3	0.76	150	UUU0J470MCL1GS
	56	5×5.8	0.26	3.528	0.76	150	UUU0J560MCL1GS
	68	6.3×5.8	0.26	4.284	0.44	230	UUU0J680MCL1GS
	100	6.3×5.8	0.26	6.3	0.44	230	UUU0J101MCL1GS
	150	6.3×5.8	0.26	9.45	0.44	230	UUU0J151MCL1GS
	220	6.3×5.8	0.26	13.86	0.44	230	UUU0J221MCL1GS
	330	6.3×7.7	0.26	20.79	0.34	280	UUU0J331MCL1GS
	470	8×10	0.28	29.61	0.17	450	UUU0J471MNL1GS
	680	8×10	0.28	42.84	0.17	450	UUU0J681MNL1GS
	1000	8×10	0.28	63	0.17	450	UUU0J102MNL1GS
	1500	10×10	0.28	94.5	0.09	670	UUU0J152MNL1GS
10 (1A)	22	4×5.8	0.20	3	1.80	80	UUU1A220MCL1GS
	27	5×5.8	0.20	3	0.76	150	UUU1A270MCL1GS
	33	5×5.8	0.20	3.3	0.76	150	UUU1A330MCL1GS
	47	6.3×5.8	0.20	4.7	0.44	230	UUU1A470MCL1GS
	56	6.3×5.8	0.20	5.6	0.44	230	UUU1A560MCL1GS
	68	6.3×5.8	0.20	6.8	0.44	230	UUU1A680MCL1GS
	100	6.3×5.8	0.20	10	0.44	230	UUU1A101MCL1GS
	150	6.3×5.8	0.20	15	0.44	230	UUU1A151MCL1GS
	220	6.3×7.7	0.20	22	0.34	280	UUU1A221MCL1GS
	330	8×10	0.24	33	0.17	450	UUU1A331MNL1GS
	470	8×10	0.24	47	0.17	450	UUU1A471MNL1GS
	680	10×10	0.24	68	0.09	670	UUU1A681MNL1GS
	1000	10×10	0.24	100	0.09	670	UUU1A102MNL1GS
16 (1C)	15	4×5.8	0.16	3	1.80	80	UUU1C150MCL1GS
	22	5×5.8	0.16	3.52	0.76	150	UUU1C220MCL1GS
	27	5×5.8	0.16	4.32	0.76	150	UUU1C270MCL1GS
	33	6.3×5.8	0.16	5.28	0.44	230	UUU1C330MCL1GS
	47	6.3×5.8	0.16	7.52	0.44	230	UUU1C470MCL1GS
	56	6.3×5.8	0.16	8.96	0.44	230	UUU1C560MCL1GS
	68	6.3×5.8	0.16	10.88	0.44	230	UUU1C680MCL1GS
	100	6.3×5.8	0.16	16	0.44	230	UUU1C101MCL1GS
	150	6.3×7.7	0.16	24	0.34	280	UUU1C151MCL1GS
	220	6.3×7.7	0.16	35.2	0.34	280	UUU1C221MCL1GS
	330	8×10	0.20	52.8	0.17	450	UUU1C331MNL1GS
	470	8×10	0.20	75.2	0.17	450	UUU1C471MNL1GS
	680	10×10	0.20	108.8	0.09	670	UUU1C681MNL1GS

UUU

■ Dimensions

Rated Voltage (V) (code)	Rated Capacitance (μ F)	Case Size ϕ D×L(mm)	$\tan \delta$	Leakage Current (μ A) (at 20°C after 2 minutes)	Impedance (Ω) MAX. (20°C/100kHz)	Rated Ripple (mA rms) (105°C/100kHz)	Part Number
25 (1E)	10	4×5.8	0.14	3	1.80	80	UUU1E100MCL1GS
	15	5×5.8	0.14	3.75	0.76	150	UUU1E150MCL1GS
	22	5×5.8	0.14	5.5	0.76	150	UUU1E220MCL1GS
	27	6.3×5.8	0.14	6.75	0.44	230	UUU1E270MCL1GS
	33	6.3×5.8	0.14	8.25	0.44	230	UUU1E330MCL1GS
	47	6.3×5.8	0.14	11.75	0.44	230	UUU1E470MCL1GS
	56	6.3×5.8	0.14	14	0.44	230	UUU1E560MCL1GS
	68	6.3×5.8	0.14	17	0.44	230	UUU1E680MCL1GS
	100	6.3×7.7	0.14	25	0.34	280	UUU1E101MCL1GS
	150	8×10	0.16	37.5	0.17	450	UUU1E151MNL1GS
	220	8×10	0.16	55	0.17	450	UUU1E221MNL1GS
	330	8×10	0.16	82.5	0.17	450	UUU1E331MNL1GS
	470	10×10	0.16	117.5	0.09	670	UUU1E471MNL1GS
35 (1V)	4.7	4×5.8	0.12	3	1.80	80	UUU1V4R7MCL1GS
	10	5×5.8	0.12	3.5	0.76	150	UUU1V100MCL1GS
	15	5×5.8	0.12	5.25	0.76	150	UUU1V150MCL1GS
	22	5×5.8	0.12	7.7	0.76	150	UUU1V220MCL1GS
	27	6.3×5.8	0.12	9.45	0.44	230	UUU1V270MCL1GS
	33	6.3×5.8	0.12	11.55	0.44	230	UUU1V330MCL1GS
	47	6.3×5.8	0.12	16.45	0.44	230	UUU1V470MCL1GS
	56	6.3×7.7	0.12	19.6	0.34	280	UUU1V560MCL1GS
	68	6.3×7.7	0.12	23.8	0.34	280	UUU1V680MCL1GS
	100	8×10	0.14	35	0.17	450	UUU1V101MNL1GS
	150	8×10	0.14	52.5	0.17	450	UUU1V151MNL1GS
	220	8×10	0.14	77	0.17	450	UUU1V221MNL1GS
	330	10×10	0.14	115.5	0.09	670	UUU1V331MNL1GS
50 (1H)	1	4×5.8	0.12	3	5.00	30	UUU1H010MCL1GS
	2.2	4×5.8	0.12	3	5.00	30	UUU1H2R2MCL1GS
	3.3	4×5.8	0.12	3	5.00	30	UUU1H3R3MCL1GS
	4.7	5×5.8	0.12	3	1.52	85	UUU1H4R7MCL1GS
	10	6.3×5.8	0.12	5	0.88	165	UUU1H100MCL1GS
	15	6.3×5.8	0.12	7.5	0.88	165	UUU1H150MCL1GS
	22	6.3×5.8	0.12	11	0.88	165	UUU1H220MCL1GS
	27	6.3×7.7	0.12	13.5	0.68	185	UUU1H270MCL1GS
	33	6.3×7.7	0.12	16.5	0.68	185	UUU1H330MCL1GS
	47	6.3×7.7	0.12	23.5	0.68	185	UUU1H470MCL1GS
	56	8×10	0.14	28	0.34	300	UUU1H560MNL1GS
	68	8×10	0.14	34	0.34	300	UUU1H680MNL1GS
	100	8×10	0.14	50	0.34	300	UUU1H101MNL1GS
	150	10×10	0.14	75	0.18	670	UUU1H151MNL1GS
	220	10×10	0.14	110	0.18	670	UUU1H221MNL1GS

- Taping specifications are given in page 20.
- Recommended land size, soldering by reflow are given in page 16, 17.
- Please refer to page 3 for the minimum order quantity.