

Resin Molded Chip Type Capacitors Series SY1, SY2, SY3, SY4, SY5, SY6, SY7, SY8, SY9 & SYF

Standard Ratings Rated Voltage 2.5V

Rated voltage (V)	Capacitance (μF) (120Hz)	Marking (P, A2, A)	EIA size code	ELNA size code	ELNA series code	Leakage current (μA, or less)	Tangent of the loss angle (less)(120Hz)				E.S.R.(Ω) (less) (100kHz)	Environmental Type ELNA Part No.	Former Type ELNA Part No.	Taping Minimum packing pcs. (pcstrl)	note
							-55°C	20°C	85°C	125°C					
2.5	4.7	e475	3216L	A2	SYF	0.50	0.12	0.08	0.10	0.12	8.0	SYF-0E475M-RA2	SKF-0E475M-RA2	3,000	*
	6.8	e685	3216L	A2	SYF	0.50	0.12	0.08	0.10	0.12	8.0	SYF-0E685M-RA2	SKF-0E685M-RA2	3,000	*
	10	e106	3216L	A2	SYF	0.50	0.12	0.08	0.10	0.12	4.0	SYF-0E106M-RA2	SKF-0E106M-RA2	3,000	*
	15	e156	3216L	A2	SYF	0.50	0.18	0.12	0.16	0.18	4.0	SYF-0E156M-RA2	SKF-0E156M-RA2	3,000	*
	15	e156	3216	A	SY3	0.50	0.09	0.06	0.08	0.09	4.0	SY3-0E156M-RA	SK3-0E156M-RA	2,000	*
	22	e226	3216L	A2	SYF	0.55	0.18	0.12	0.16	0.18	4.0	SYF-0E226M-RA2	SKF-0E226M-RA2	3,000	*
	22	e226	3216	A	SY4	0.55	0.12	0.08	0.10	0.12	2.0	SY4-0E226M-RA	SK4-0E226M-RA	2,000	*
	33	e336	2012	P	SYF	0.82	0.12	0.08	0.10	0.12	4.0	SYF-0E336M-RP	—	3,000	
	33	e336	3216L	A2	SYF	0.82	0.18	0.12	0.16	0.18	4.0	SYF-0E336M-RA2	SKF-0E336M-RA2	3,000	
	33	e336	3216	A	SY5	0.82	0.12	0.08	0.10	0.12	2.0	SY5-0E336M-RA	SK5-0E336M-RA	2,000	
	47	e476	3216L	A2	SYF	1.17	0.18	0.12	0.16	0.18	4.0	SYF-0E476M-RA2	SKF-0E476M-RA2	3,000	
	47	e476	3216	A	SY6	1.17	0.18	0.12	0.16	0.18	2.0	SY6-0E476M-RA	SK6-0E476M-RA	2,000	
	68	e686	3216	A	SY7	1.70	0.21	0.14	0.19	0.21	2.0	SY7-0E686M-RA	SK7-0E686M-RA	2,000	
	68	—	3528	B	SY5	1.70	0.12	0.08	0.10	0.12	1.0	SY5-0E686M-RB	SK5-0E686M-RB	2,000	*
	100	e107	3216	A	SY8	2.50	0.24	0.16	0.19	0.24	2.0	SY8-0E107M-RA	SK8-0E107M-RA	2,000	
	100	—	3528	B	SY6	2.50	0.12	0.08	0.10	0.12	1.0	SY6-0E107M-RB	SK6-0E107M-RB	2,000	
	150	—	3528	B	SY7	3.75	0.18	0.12	0.16	0.18	1.0	SY7-0E157M-RB	SK7-0E157M-RB	2,000	
	220	—	3528	B	SY8	5.50	0.27	0.18	0.23	0.27	1.0	SY8-0E227M-RB	SK8-0E227M-RB	2,000	

The asterisk in the Remarks row indicates the reduced frequency of manufacture due to miniaturization, etc.
For new design, it is recommended to choose a smaller product with a higher voltage and same capacity.

NOTE

Design, Specifications are subject to change without notice.
Ask factory for technical specifications before purchase and/or use.

Resin Molded Chip Type Capacitors Series SY1, SY2, SY3, SY4, SY5, SY6, SY7, SY8, SY9 & SYF

Standard Ratings Rated Voltage 35V

Rated voltage (V)	Capacitance (μF) (120Hz)	Marking (P, A2, A)	EIA size code	ELNA size code	ELNA series code	Leakage current (μA , or less)	Tangent of the loss angle (less)(120Hz)				E.S.R. (Ω) (100kHz)	Environmental Type ELNA Part No.	Former Type ELNA Part No.	Taping Minimum packing pcs. (pcstrl)	note
							-55°C	20°C	85°C	125°C					
35	0.10	V104	3216	A	SY1	0.50	0.09	0.05	0.08	0.09	28.0	SY1-1V104M-RA	SK -1V104M-RA	2,000	
	0.15	V154	3216	A	SY1	0.50	0.09	0.05	0.08	0.09	24.0	SY1-1V154M-RA	SK -1V154M-RA	2,000	
	0.22	V224	3216	A	SY1	0.50	0.09	0.05	0.08	0.09	20.0	SY1-1V224M-RA	SK -1V224M-RA	2,000	
	0.33	V334	3216	A	SY1	0.50	0.09	0.05	0.08	0.09	15.0	SY1-1V334M-RA	SK -1V334M-RA	2,000	
	0.47	V474	3216	A	SY2	0.50	0.09	0.05	0.08	0.09	11.0	SY2-1V474M-RA	SK2-1V474M-RA	2,000	
	0.47	—	3528	B	SY1	0.50	0.09	0.04	0.06	0.09	11.0	SY1-1V474M-RB	SK -1V474M-RB	2,000	
	0.68	V684	3216	A	SY2	0.50	0.09	0.04	0.06	0.09	8.0	SY2-1V684M-RA	SK2-1V684M-RA	2,000	
	0.68	—	3528	B	SY1	0.50	0.09	0.04	0.06	0.09	8.0	SY1-1V684M-RB	SK -1V684M-RB	2,000	
	1.0	V105	3216	A	SY3	0.50	0.09	0.06	0.08	0.09	7.0	SY3-1V105M-RA	SK3-1V105M-RA	2,000	
	1.0	—	3528	B	SY1	0.50	0.09	0.04	0.06	0.09	6.0	SY1-1V105M-RB	SK -1V105M-RB	2,000	
	1.5	V155	3216	A	SY4	0.52	0.09	0.06	0.08	0.09	4.0	SY4-1V155M-RA	SK4-1V155M-RA	2,000	
	1.5	—	3528	B	SY2	0.52	0.09	0.06	0.08	0.09	5.0	SY2-1V155M-RB	SK2-1V155M-RB	2,000	
	1.5	—	6032	C	SY1	0.52	0.09	0.06	0.072	0.09	4.5	SY1-1V155M-RC	SK -1V155M-RC	500	
	2.2	—	3528	B	SY3	0.77	0.09	0.06	0.08	0.09	4.0	SY3-1V225M-RB	SK3-1V225M-RB	2,000	
	2.2	—	6032	C	SY1	0.77	0.09	0.06	0.072	0.09	3.5	SY1-1V225M-RC	SK -1V225M-RC	500	
	3.3	—	3528	B	SY4	1.15	0.09	0.06	0.08	0.09	4.0	SY4-1V335M-RB	SK4-1V335M-RB	2,000	
	3.3	—	6032	C	SY1	1.15	0.09	0.06	0.072	0.09	3.0	SY1-1V335M-RC	SK -1V335M-RC	500	
	4.7	—	6032	C	SY2	1.64	0.09	0.06	0.08	0.09	2.0	SY2-1V475M-RC	SK2-1V475M-RC	500	
	4.7	—	7343	D0	SY1	1.64	0.09	0.06	0.072	0.09	1.5	SY1-1V475M-RD0	SK -1V475M-RD0	500	
	6.8	—	6032	C	SY3	2.38	0.09	0.06	0.08	0.09	2.3	SY3-1V685M-RC	SK3-1V685M-RC	500	
	6.8	—	7343	D0	SY1	2.38	0.09	0.06	0.072	0.09	1.3	SY1-1V685M-RD0	SK -1V685M-RD0	500	
	10	—	6032	C	SY4	3.50	0.09	0.06	0.072	0.09	1.5	SY4-1V106M-RC	SK4-1V106M-RC	500	
	10	—	7343	D0	SY2	3.50	0.09	0.06	0.08	0.09	1.0	SY2-1V106M-RD0	SK2-1V106M-RD0	500	
	15	—	7343	D0	SY3	5.25	0.09	0.06	0.08	0.09	1.0	SY3-1V156M-RD0	SK3-1V156M-RD0	500	
	22	—	7343	D0	SY4	7.70	0.12	0.08	0.10	0.12	0.7	SY4-1V226M-RD0	SK4-1V226M-RD0	500	

The asterisk in the Remarks row indicates the reduced frequency of manufacture due to miniaturization, etc.
For new design, it is recommended to choose a smaller product with a higher voltage and same capacity.

NOTE

Design, Specifications are subject to change without notice.
Ask factory for technical specifications before purchase and/or use.