

Residual-current circuit breaker trip block for AZ, 125A, 4pole, 1000mA, type S/A



**Part no. FBH MV-125/4/1-S/A
170176**

Product name	Eaton Moeller series xEffect - FBHmV RCCB add-on unit
Part no.	FBH MV-125/4/1-S/A
EAN	4015081666850
Product Length/Depth	94.5 millimetre
Product height	80 millimetre
Product width	90 millimetre
Product weight	0.528 kilogram
Compliances	RoHS conform
Certifications	IEC 61373 EN45545-2 IEC/EN 60947-2
Product Tradename	FBHmV
Product Type	RCCB add-on unit
Product Sub Type	None
Application	Switchgear for industrial and advanced commercial applications xEffect - Switchgear for industrial and advanced commercial applications
Number of poles	Four-pole
Tripping time	Selective switch off 40 ms delayed - selective switch off
Amperage Rating	125 A
Rated short-circuit strength	Same as connected AZ
Fault current rating	1000 mA
Sensitivity type	AC and pulsating DC current sensitive
Impulse withstand current	Surge-proof 5 kA
Type	Add-on residual current protection unit FBHmV Type S/A
Voltage rating - min	240 V
Voltage rating - max	415 V
Rated operational voltage (Ue) - max	415 V
Rated insulation voltage (Ui)	440 V
Rated impulse withstand voltage (Uimp)	4 kV
Rated fault current - min	1 A
Rated fault current - max	1 A
Frequency rating	50 Hz
Leakage current type	A
Rated short-time withstand current (Icw)	0 kA 10 kA
Surge current capacity	5 kA
Pollution degree	2
Lifespan, electrical	1000 operations
Frame	45 mm
Width in number of modular spacings	5.5
Built-in width (number of units)	95 mm (5.5 SU)
Built-in depth	70 mm
Mounting Method	DIN rail Screwed onto AZ 2-, 3-, 4-pole; Z-BHASA
Degree of protection	IP20

		IP20, IP40 with suitable enclosure
Terminals (top and bottom)		Lift terminals
Connectable conductor cross section (solid-core) - min		2.5 mm ²
Connectable conductor cross section (solid-core) - max		50 mm ²
Connectable conductor cross section (multi-wired) - min		2.5 mm ²
Connectable conductor cross section (multi-wired) - max		50 mm ²
Terminal protection		Finger and hand touch safe, DGUV VS3, EN 50274
Lifespan, mechanical		8000 operations
Permitted storage and transport temperature - min		-35 °C
Permitted storage and transport temperature - max		60 °C
Climatic proofing		25-55 °C / 90-95% relative humidity according to IEC 60068-2
Rated operational current for specified heat dissipation (In)		125 A
Heat dissipation per pole, current-dependent		0 W
Equipment heat dissipation, current-dependent		39.7 W
Heat dissipation capacity		0 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		40 °C
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Features		Selective protection Additional equipment possible Add-on residual current protection unit
Fitted with:		Interlocking device
Special features		Ambient temperature hint: Starting at 40 °C, the max. permissible continuous current decreases by 3% for every 1 °C
Used with		Type S/A FBHmV Add-on residual current protection unit

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / Residual current circuit breaker (RCCB) module (EC002297)		
Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / Residual current circuit breaker (RCCB) module (ec@ss10.0.1-27-14-22-10 [ACN357011])		
Nominal voltage	V	240 - 415
Nominal current	A	125

Rated fault current adjustable		No
Rated fault current	A	1 - 1
Max. delay time	ms	40
Delay adjustable		No
Number of poles		4
Leakage current type		A
Surge current capacity	kA	5
Frequency		50 Hz
Rated insulation voltage U_i	V	440
Rated impulse withstand voltage U_{imp}	kV	4
Connectable conductor cross section solid-core	mm ²	2.5 - 50
Connectable conductor cross section multi-wired	mm ²	2.5 - 50
Anti- nuisance tripping version		No
With interlocking device		Yes
Degree of protection (IP)		IP20
Pollution degree		2
Ambient temperature during operating	°C	-25 - 40